


Quick Start Guide QUESTIONS? visit www.ihome.com or call 1-800-288-2792

BACK PANEL USB Charging Port DST Switch (5V/IA) LEFT PANEL RIGHT PANEL TOP PANEL BOTTOM PANEL

FEATURES & FUNCTIONS



GETTING STARTED

Step One Connecting the Unit

Before use, remove the battery pull tab from the bottom of the unit. Connect the included AC adapter to the DC lack located on the back of the unit and connect the other end to a working wall outlet.



To toggle the clock display

while the display is flashing

hetween 12/24 hour time

press the Alarm Button

during time setting.

Step Two etting Your Clock · Press and hold the Time Set

- Button until the display flashes. . Press the = or + Buttons to adjust selections and press Time Set to
- confirm · Do this for time, year, month and
- date All done!

Daylight Savings Time (DST) Switch:

By default, the DST Switch is set to Auto and will automatically adjust the time each March and November.

DISPLAY ICONS



To adjust the brightness of the display press the Time Set Button repeatedly to cycle through brightness settings, including OFF.

SETTING THE ALARM

Note: Each step must be completed while display is flashing or setting will time-out with any changes saved. 1. Press and hold the Alarm Button for 2 seconds until the alarm time

- display and alarm icon flash. 2. Press the - or + Buttons to adjust the alarm time to the desired time
- (hold for rapid setting). Make sure you set the correct AM/PM alarm time. The PM indicator appears to the left of the display.
- 3. Press the Alarm Button to confirm the alarm time setting. The alarm schedule will flash: 7 (every day), 5 (weekdays) or 2 (weekend only). Press the - or + Buttons to select the desired alarm schedule. 4 Press the Alarm Button to confirm the alarm schedule 2 beens will confirm alarm setting is complete. The alarm icon will remain on the
- 5. To turn off a sounding alarm and reset it to come on the next day at the same time, press the Alarm Button to reset alarm.

PREVIEWING THE ALARM

display indicating the alarm is armed

Press and release the desired Alarm Button as needed to preview the alarm and to toggle the alarm ON (indicated by the alarm icon) or OFF (no alarm icon)

PROGRAMMABI E SNOOZE

- 1. To program Snooze, press down on the front of the unit for 2 seconds during normal operation (when no alarm is
- sounding) 2. Press the - or + Buttons to select a snooze time (between 01 and
- 3. Press down and release the front of the unit to confirm setting. While the alarm is sounding, press down on the front of the unit to temporarily silence the alarm (9 minutes is the default). Snooze can be used several times during the one hour alarm cycle.

WIRELESS CHARGING

 Qi compatible phones (also works with plastic cases up to 3mm thick) · AirPods with wireless charging case Place Qi compatible device face up on the charging rest as pictured below.



Slow blinking Ficon: Device is charging properly.

Solid 7 icon: Device is charged. Rapid blinking F icon: Device is not charging properly. Reposition

Note: The lightning icon may continue to blink slowly when iOS devices are fully charged.

Remove metal protective or magnetic case from phone before charging. When charging phone, do not place magnetic-striped or other metal objects on the charger. Doing so could damage the object or this unit. Qi compatible phones with metallic looking finishes will charge normally.

devices)

USB CHARGING Connect the standard size end of a USB cable (not included) to the USB port on the back of the unit and connect the other end to the charging port on your device. (Make sure the unit is plugged into a



BATTERY BACK-UP The unit comes with a CR-2450 back-up battery installed to

provide continuous alarm operation and clock settings in the event of a temporary power failure. Remove the battery pull tab before use. When the battery icon on the clock display is flashing, it is time to replace the back-up battery. The battery compartment is located on the bottom of the unit

- 1. Make sure the AC adapter is connected or you will lose your time and alarm settings during battery replacement 2. Use a Phillips screwdriver to open
- the battery compartment door.
- 3. Remove the exhausted battery from the compartment and insert 1 CR-2450 battery, checking that the + side is facing you. Replace the compartment door Do not overtiahten



WARNING: Lithium batteries can explode or cause burns if disasse shorted, recharged, exposed to water, fire, or high temperatures. Do not place loose batteries in a pocket, purse, or other container containing metal objects, mix with used or other battery types, or store with hazardous or combustible materials. Store in cool, dry ventilated area. Follow applicable laws and regulations for transport and disposal

- . Do not ingest the battery, Chemical Burn Hazard. This product contains a coin/button cell battery. If the coin/button cell battery is swallowed, it car cause severe internal burns in just 2 hours and can lead to death.
- · Keen new and used batteries away from children If the battery compartment does not close securely, stop using the product and keep it away from children. If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention.
- · Attention should be drawn to the environmental aspects of battery

IMPORTANT SAFETY INSTRUCTIONS

When used in the directed manner, this unit has been designed and manufactured to ensure your sp triese instructions nandy for future reference, take special note or all warnings listed in these tructions and on the unit.

Water and Moisture - The unit should not be used near water. For example: near a bathtub.

- Water and Moisture The unit should not be used near water. For example, near a bathbub, wanthbowl, kitchen sink, laundry tut, swimming pool or in a web beasement. Ventilation The unit should be situated so that its location or position does not interfere with its proper ventilation. For example, it should not be situated on a bed, solar, rug or similar surface that may block ventilation openings. Also, it should not be placed in a built-in installation, such as a bookcase or cabinet, which may impede the flow of air through the
- Installations, such as a control of the control of stoves or other appliances (including amplifiers) that produce heat. Power Sources - The unit should be connected to a power supply only of the type described in the operating instructions or as marked on the appliance. Only use the AC adapter that came
- With the Unit.

 Power-Cable Protection Power supply cables should be routed so that they are not likely to Fower-Lable Protection - Power supply capies should be routed so that they are not likely to be walled on or pinched by items placed upon or against them. It is always best to have a clear area from where the cable exits the unit to where it is plugged into an AC socket.
- area from where the cable exists the unit to where it is blugged into an AC social configuration. Counting Cleaning with by cable. Counting Cleaning with by cable. Counting Cleaning with the cable of the cable of

- over-line surges.

 Overloading Do not overload well sockets, extension cords, or integral convenience receptacles as this can result in a risk of fire or electric shock.
- recognizations as the can result in a risk of the or electric shock.

 The control of the can result is a result of the control of the control
- month or longer, remove batteries before storage

 13. Servicing The user should not attempt to service the unit beyond those methods described in the user manual. Service methods not covered in the operating instructions should be
- red to qualified service personnel. eterred to qualitied service personner. Agenetic Interference: This product's speakers contain powerful magnets which could cause lagnetic interference: This product's speakers contain powerful magnets which could cause terference or dismage to sensitive equipment such as hard drives, CRT televisions and ponitors, as well as medical, scientific, and navigational devices. Keep this true away from these
- monitors, as well as medical, scientific, and navigational devices, keep this unit away monitor as an opportunit as all litimes.

 Only use attachments/accessories specified by the manufacturer. This product is suitable for use in tropical and/or moderate climates.

 The unit should be serviced by qualified service personnel when the enclosure damaged or
- s not operate normally. naked flame sources, such as lighted candles, should be placed on the apparatus. RNING: To reduce the risk of fire or electric shock, do not expose this product to rain or moisture CAUTION - Danger of explosion if battery is incorrectly replaced. Replace only with the same or equivalent type.
- 21. The mains plug of power adaptor is used as the disconnect device, it shall remain readily

FCC INFORMATION

Model: iW18 CID: EMOIW18 IC: 9868-IW18

his device compiles with Part 15 of the FCC Rules, operation is subject to the following two onditions: (1) This device may not cause harmful interference, and (2) this device must accept ny interference received, including interference that may cause undesired operation.

IC Statement

WARRANTY

For product support information and warranty please visit: www.ihome.com/support

© 2019 SDI Technologies Inc. All rights reserved

Questions? Visit www.ihome.com or call 1-800-288-2792 Toll Free